



# Bindings

Help Documentation

## **Bindings**

### **IP Addresses**

System administrators can use this section to specify on which ports the IPs on the server should listen. All ports being used should be assigned to at least one IP. However, SmarterMail provides system administrators with some flexibility when configuring IP bindings. This means, for example, that the system administrator can allow POP on the IP 111.111.111.11 but not on the IP 222.222.222.22. In addition, some servers may have other programs installed that need to listen on mail ports. To accommodate this, the system administrator can configure SmarterMail to listen on a subset of IP addresses, leaving the remaining IP addresses available for other programs.

Another benefit to binding IPs to your mail server is that you can limit the possibility of your entire mail server being blacklisted by assigning IPs on a per domain basis. That means that spammers sending messages on your mail server will only get their domain and their specific IP blacklisted rather than getting the entire mail server blocked.

To access the IP address settings, click the settings icon and expand the Bindings folder in the navigation pane. Then click IP Addresses . A list of IP addresses on the server will load in the content pane and the following options will be available in the content pane toolbar:

- Edit - Edits the ports assigned to the selected IP.

### **Ports**

System administrators can use this section to configure the ports that can be assigned to IPs. In addition, this section is used to add Secure Socket Layer (SSL) and Transport Layer Security (TLS) rules.

To access the port settings, click the settings icon and expand the Bindings folder in the navigation pane. Then click Ports . A list of ports will load in the content pane and the following options will be available in the content pane toolbar:

- New - Creates a new port.
- Edit - Edits the selected port options.
- Delete - Permanently deletes the selected port(s).

### **Creating New Ports**

When adding a new port there are several fields that need to be completed. These fields are:

- Name - The friendly name for the port.
- Port - The port number on which to listen for the selected protocol.
- Type - The type of communications protocol that should be used (SMTP, IMAP, LDAP, POP or submission port).
- Description - A simple description of the port and/or the port name.
- SSL/TLS - If the port requires SSL or TLS encryption, check the appropriate option. SSL always assumes the connection will be secure and sends the encryption immediately. TLS connects normally and then looks to see if the connection is secure before sending the encryption.

## Hostnames

This feature allows administrators to assign a hostname for each IP address. For example: IP 1.1.1.1 can be assigned to mail.domain1.com and IP 1.1.1.2 can be for mail.domain2.com.

To view hostnames, click the manage icon and click Hostnames in the navigation pane. A list of hostnames will load in the content pane and the following options will be available from the content pane toolbar:

- New - Creates a new hostname.
- Edit - Edits the selected hostname.
- Delete - Deletes the selected hostname(s).