



# Anti

Help Documentation

## Antivirus Administration

SmarterMail is equipped with effective and self-updating ClamAV antivirus protection out-of-the-box. In addition, SmarterMail can support additional third-party solutions that include a quarantine directory. SmarterMail has the ability to check the quarantine directory and respond to users that attempted to send an email containing a virus.

To view the antivirus settings for your server, click the Security button in the main toolbar and then click Antivirus Administration in the left tree view. The antivirus settings will load in the content pane and the following tabs will be available:

### Options

- Enable ClamAV - Select this checkbox to enable ClamAV.
- Enable Real-Time AV - Select this checkbox to enable Real-Time AV.
- Enable Command-Line AV - Select this checkbox to enable a command-line virus scanner.

### ClamAV

Clam AntiVirus is a third-party open source antivirus toolkit, designed especially for scanning email on mail gateways. For more information on ClamAV, visit: [www.clamav.com](http://www.clamav.com)

- IP Address - The IP address of the ClamAV server to use.
- Port - The port that the ClamAV server is listening on.
- Remote Server - Select this checkbox if the server is a remote server.
- Timeout - The maximum number of seconds to wait before moving on. By default, the timeout is 10 seconds.
- Failures Before Disable - The maximum number of timeouts allowed before ClamAV is disabled. By default, ClamAv is limited to 5 failures.
- Virus Definitions - The date and time the virus definitions were last updated. The definitions are updated whenever the service starts and every 6 hours thereafter. To manually update virus definitions, click Update ClamAV in the actions toolbar.

### Real-Time AV

- Quarantine Directory - The full path to the quarantine directory for the server.
- Virus Action - The action taken when an email contains a virus. The available actions are:
  - Delete - Deletes any files attached to the message from the spool directory. This does not take any action on the quarantine directory.
  - Inform Sender - Informs the "From" address that a message was received by the server, and because a virus was found in the message, it did not reach the intended recipient. Note: With

some of the more recent viruses, this action becomes less useful, as many viruses now spoof the "From" email address.

## **Command-line AV**

- Command Line - The command that you want to execute. %FILEPATH will be replaced with the path to the file to be scanned.

## **CommTouch Zero-hour Antivirus**

The CommTouch Zero-hour Antivirus add-on uses Recurrent Pattern Detection technology to identify identifies viruses based on their unique distribution patterns and provides a complementary shield to conventional AV technology, protecting in the earliest moments of malware outbreaks and continuing protection as each new variant emerges.

CommTouch evaluates each message and determines the probability that the message contains a virus. System administrators can choose the default action taken on a message when CommTouch determines the it has a medium, high, or definite probability of containing a virus. For more information, or to purchase this add-on, visit the SmarterTools website .