



Email Report Settings

Help Documentation

Email Settings

This feature is only available to site administrators using SmarterStats Enterprise.

Site administrators can use this section to customize how SmarterStats sends scheduled email reports. To use the default values set by your system administrator, leave the options on this page blank.

To access this section, click the Settings icon. Then expand the Site Settings folder and click Email Settings in the navigation pane. The email settings will load in the content pane and the following options will be available.

- From Address - The email address from which reports will be sent.
- SMTP Server - The mail server that will be used to email reports. Note: If you wish to use a port other than 25 for your SMTP Server, include it after the server name or IP with a colon. For example, if your mail server is mail.example.com and it listens on port 10000, use mail.example.com:10000 as the server name.
- From Display Name - The friendly name that emails sent from SmarterStats will show as being sent from.
- SMTP Server - The name or IP Address of the server SmarterStats should send email from.
- SMTP Server Port - The port number that should be used when sending email through SMTP. In most cases, the SMTP server port is 25.
- Enable secure sockets layer (SSL) - Select this option if your server requires SSL authentication.
- Enable SMTP Authentication - Select this option if SMTP authentication is required to send mail from this email address.
- Auth Username - The identifier used to authenticate with the SMTP server. In some cases, this may be the full email address of the account.
- Password - The corresponding password used to authenticate with the SMTP server.